Safety data sheet PLA

Ultimaker It's in the making

1. Identification of the substance/preparation and of the company

1.1 Trade name	PLA	
1.2 Use of the product	3D-Printer filament	
1.3 Supplier	Ultimaker (Watermolenweg 2, 4191PN, Geldermalsen, The Netherlands)	
Emergency phone number	In case of toxicological emergency contact your doctor	
2. Hazards identification according to regulation (EC) No 1272/2008 and GHS		

No risk exists to the health of users if the product is 2.1 Classification of the substance or mixture handled and processed properly 2.2 Label elements Labelling Not applicable 2.3 Other hazards Not known 3. Composition/information on ingredients 3.1 Composition Polylactic acid 3.2 Mixture Not applicable 4. First aid measures 4.1 Description of first aid measures General advice: If you feel unwell, seek medical advice (show the label where possible). Never give anything by mouth to an unconscious person Inhalation In case of inhalation of gases released from molten filament, move person into fresh air Skin contact Wash with soap and water. Seek medical attention if symptoms occur. If burned by contact with hot material, cool molten material adhering to skin as quickly as possible with water, do not try to peel it off and seek for medical attention, if necessary, for removal and treatment of the burns

Eye contact	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. Seek medical attention if symptoms persist. If molten material contacts the eye, immediately flush with plenty of water for at least 15 minutes. Seek medical attention immediately
Ingestion	Not probable. Seek medical advice in case ingestion occurs
Note to physician	Treat symptomatically
4.2 Most important symptoms and effects, both acute and delayed	Burns should be treated as thermal burns. The material will come off as healing occurs; therefore immediate removal from skin is not necessary
4.3 Indication of any immediate medical attention and special treatment needed	No data available
5. Firefighting measures	Material can accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or grounding procedures
5.1 Extinguishing media	Foam, carbon dioxide (CO ₂), water, dry chemical. Alcohol resistant foams are preferred if available. General-purpose synthetic foams (including AFFF) or protein foams may function but much less effective
	Unsuitable extinguishing media: not known
5.2 Special hazards arising from the substance or mixture	Burning produces obnoxious and toxic fumes: aldehydes, carbon oxides (CO_x)
5.3 Advice for firefighters	Use self-contained breathing apparatus and full protective clothing
6. Accidental release measures	
6.1 Personal precautions, protective equipment and emergency procedures6.2 Environmental precautions	Avoid breathing gases released from molten filament. Ensure adequate ventilation, especially in confined areas
6.3 Methods and materials for containment and cleaning	No data available
up 6.4 Reference to other sections	Allow to solidify molten material. Dispose of waste and residue in accordance with local regulations
	-
7. Handling and storage	
7.1 Precautions for safe handling	Avoid contact with molten material
7.2 Conditions for safe storage, including any incompatibilities	Product should be stored in a dry and cool place at temperatures between -20 to +30 °C. Avoid direct sunlight. Minimize moisture uptake by leaving it in a sealed package together with the supplied desiccant
7.3 Specific end use(s)	Filament for 3D printing

8. Exposure controls/personal protection

8.1 Control parameters	None
DNEL:	No data available
PNEC:	No data available
8.2 Exposure controls	
Eye protection	Use safety glasses for prolongated stare at printing
Skin and body protection	Good practices suggest to minimize skin contact. When material is heated, wear gloves to protect against thermal burns
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (when applicable) or to an acceptable level (in countries where exposure limits have not been established) an approved respirator must be worn. Respirator type: air-purifying respirator with an appropriate government approved (where applicable) air purifying filter, cartridge or canister. Contact a health and safety professional or manufacturer for specific information
Hand protection	Follow good industrial hygiene practices
Hygiene measures	Follow good industrial hygiene practices
Engineering measures	Good general ventilation (typically 10 air changes per hour) is recommended. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls that maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance
Color
Odor
Flash point
Ignition temperature
Thermal decomposition
Auto-ignition temperature
Melting point/range
Density
Water solubility
Solubility in other solvents

9.2 Other information

Filament Various (incl. transparent) Slight -388 °C

250 °C

145-160 °C 1.24 g/cm³ Insoluble Chloroform smoothable

10. Stability	Stable under recommended storage conditions
10.1 Reactivity	No data available
10.2 Chemical stability	Biodegradable
10.3 Possibility of hazardous reactions	No decomposition or hazardous reactions if stored and applied as directed
10.4 Conditions to avoid	Print temperatures above 240 °C (at standard printing speeds)
10.5 Incompatible materials	Oxidizing agents, strong bases
10.6 Hazardous decomposition products	See 5.2
11. Toxicological information	
11.1 Information on toxicological effects	
Principle routes of exposure	Eye contact, skin contact, inhalation, ingestion
Acute toxicity	There were no target organ effects noted following ingestion or dermal exposure in animal studies
Skin corrosion/irritation	May cause eye/skin irritation. Product dust may be irritating to eyes, skin and respiratory system. Caused mild to moderate conjunctival irritation in eye irritation studies using rabbits. Caused very mild redness in dermal irritation studies using rabbits (slightly irritating)
Serious eye damage/eye irritation	No data available
Respiratory or skin sensitization	No data available
Reproductive toxicity	No data available
Carcinogenicity	No data available
12. Ecological information	
12.1 Toxicity	No data available
12.2 Persistence and degradability	-
12.3 Bio accumulative potential	Does not bio accumulate
12.4 Mobility in soil	No data available
12.5 Results of PBT and vPvB assessment	No data available
12.6 Other adverse effects	No data available
13. Disposal considerations	
13.1 Waste treatment methods	In accordance with local and national regulations

14. Transport information

ADR RID IATA IMDG Special precautions for user

15. Regulatory information

15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture

US Regulations:

Sara 313 title III TSCA inventory list OSHA hazard category CERCLA WHMIS State right-to-know requirements

Other inventories:

Canada DSL inventory list REACH/EU EINIECS NEHAPS Japan (ECL/MITI) Australia (AICS) Korean toxic substances control act (ECL) Philippines inventory (PICCS) Chinese chemical inventory (IECSC)

15.2 Chemical safety assessment

16. Other information

Not regulated Not regulated Not regulated Not regulated Not regulated

Not meant to be all inclusive - selected regulations represented

Not listed Listed ------Listed Components are in compliance with REACH and/or are listed -Listed Listed Listed Not listed Listed

No data available

The information provided in this Safety Data Sheet (SDS) is based on current knowledge and experience. This information is provided without warranty. This information should help to make an independent determination of the methods to ensure proper and safe use and disposal of the filament

Version

Date

Version 3.003 18/10/2016

